


Huijue Optical Cable Gyta53-24 Core 3000m



Huijue Optical Cable Gyta53-24 Core 3000m



These products are designed to ensure the accuracy, efficiency, and reliability of fiber optic networks. Fiber Cable and Accessories: The second series comprises



In the GYTA53 cable, single-mode/multimode fibers are positioned in the loose tubes, the tubes are filled with water blocking filling compound. Tubes and fillers are stranded around the strength member into



Deploy robust fiber networks underground with our GYTA53 Direct Buried Fiber Optic Cable. Featuring a Double Jacket (PE) and Double Armor (Aluminum +



Durable 24-core GYTA53 fiber optic cable with double steel/aluminum armor for harsh underground/duct installations. Moisture-proof, rodent-resistant, high tensile strength.



Structure of 24 Cores GYTA53 Fiber Optic Cable. There are numerous features of the 24 Cores GYTA53 Fiber Optic Cable and you can easily identify it in the




Armored Loose Tube Double/Single Jacket Armor fiber optic cables are designed to provide high fiber counts with the flexibility and versatility required for today's



3. Packaging & Delivery All cables will be delivered on drums with protection of both ends of the cable. Each drum will have a waterproof mark according to requirements. Normal cable length: 2~3 km, or



GYTA53 fiber optic outdoor cable is with corrugated steel tape and aluminum tape armored and double sheath, suitable for direct buried installation.



Packaging and delivery Packaging Details Fiber Optic Cable Gyta53's packing way: 1. Wooden reel, 1000m/reel, 2000m/reel, 3000m/reel, customer's requirements are also welcomed;

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.abcstimulo.fr>

Email: contact@abcstimulo.fr

Phone: +48 539 742 186

Address: 15 Rue de la Photonique, 69100 Villeurbanne, Auvergne-Rhône-Alpes, France

This document is for informational purposes only. Specifications subject to change without notice.

